



**HANGERS:**

X= (60)LUS28  
 O= (12)THJA26  
 U=  
 D=  
 \* =

**BEAM LEGEND:**

BM1=  
 BM2=  
 BM3=  
 BM4=  
 BM5=

**NOTES:** CONTRACTOR IS RESPONSIBLE FOR PROPER SUPPORT OF ALL BEAMS & GIRDERS!!

**FLOORS:**  
 1) TRUSSES MAY BE ADJUSTED UP TO 3 1/2" TO ALLOW FOR PLUMBING.  
 2) ALIGN CHASE AS SHOWN BY HATCHING.  
**ROOFS:**  
 1) HATCHED AREA INDICATES VOLUME CLG.

DEPTH/PITCH: 6:12  
 OVERHANGS: 16 1/2"  
 CLG PITCH: —  
 OC SPACING: 24" OC

-----WARNING-----  
 DO NOT SET TRUSSES WITHOUT READING HIB-91 BRACING BROCHURE PROVIDED WITH THIS ORDER.  
**DO NOT CUT OR REPAIR TRUSSES WITHOUT WRITTEN APPROVAL FROM TINDELL'S**

CUSTOMER:	
JOB:	LOT #: UNIT:
DESIGNED FROM PLANS DATED:	
<b>TINDELL'S TRUSS DIVISION</b> 2612 BYINGTON-SOLWAY KNOXVILLE, TN 37921	
SCALE: 1/8" = 1'-0"	DRAWN BY: BRUCE
DATE: 11/4/04	LAYOUT TYPE: ROOF
ORDER #: 1089035	